



REINVENT HOW THE WORLD CLEANS

T291

Small walk-behind scrubber-dryer

Big value in a small size

Get a lot of value in a small scrubber-dryer with intuitive controls, comfortable ergonomics, and straight-forward operation. Daily maintenance is made easy due to a large recovery tank lid opening, no-tool brush/pad replacement, and yellow touchpoints. Perfect for facility owners and operators who want a productive, easy-to-use machine that is also easy to maintain.

Available technologies



ec-H2O NanoClean® with chemical dosing system



Comfortable & easy to maneuver

Optimize operator comfort with great maneuverability and an adjustable handle with comfortable grip for ergonomic operation.



Easy operation

Operate with ease and simplify operator training using pre-programmed cleaning settings.



Extend cleaning uptime

Reduce noise levels and water consumption while increasing run time with ECO mode.

Inside the T291

- 1. Self-leveling brush technology** for optimum cleaning performance on various surfaces.
- 2. Intuitive controls** featuring pre-programmed cleaning settings, standard and ECO mode, make it easy to operate and train.
- 3. Large LCD display** with clear controls and multilingual support allows users to monitor helpful information.
- 4. Large sized recovery tank opening** enables full access and visibility to help simplify daily maintenance.
- 5. Effective squeegee design** and standard Linatex® blades offer excellent water pick-up.
- 6. No-tool brush/pad change system** simplifies maintenance with the ability to spin-on and spin-off from the operator controls.
- 7. Yellow touch points** help simplify operator training and daily preventative maintenance.
- 8. On-board charger** allows for flexible charging.



T291 specifications

SPECIFICATION

FEATURE	PAD ASSIST	SELF-PROPEL	SELF-PROPEL	SELF-PROPEL
Cleaning path		550mm	600 mm	700 mm
Productivity (per hour) theoretical max	1967 m ² /hr	2468 m ² /hr	2697 m ² /hr	3142 m ² /hr
Estimated coverage (per hour)*	1246 m ² /hr	1564 m ² /hr	1724 m ² /hr	2035 m ² /hr
Scrubbing speed	3.5 kmh		4.5 kmh	
Scrub head raise/lower		manual with foot pedal		electronic by actuator
Brush/pad speed		150 rpm		200 rpm
Brush/pad pressure		19 kg	29 kg	35.4kg
Solution tank capacity			50 L	
Recovery tank capacity			50 L	
Battery run time - up-to hours**	2.5		3.5	
Battery voltage			24V (2x12)	
Dimensions (L x W x H)	1327 x 563 x 1033 mm		1297 x 653 x 1033	1297 x 735 x 1033
Squeegee width		772 mm		940 mm
Weight (with heaviest battery)	150 kg	178 kg	183 kg	187 kg
Sound level (operator's ear)***			56 dB	
Chemical dosing		Standard with ec-H2O NanoClean® technology		

Specifications subject to change without notice.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information, call **+32 3 217 94 11** or email **europe@tennantco.com**