



IPC

BY TENNANT COMPANY



GS 3/78 OIL

EXCLUSIVE FEATURES

- ▶ INNOVATIVE GASKET
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ DRAIN HOSE
- ▶ TIPPING TROLLEY
- ▶ DFS - DUAL FILTRATION SYSTEM FOR SIMULTANEOUS DRY AND WET PICK UP
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ TANGENTIAL INLET AND CONVEYOR CONE

		GS 3/78 OIL
Code		ASD015122
TECHNICAL DATA		
Usage		WET & DRY
Number of phases		single phase
Voltage / Frequency	V	220-240/50-60
N. and type of motor		3 x 2 stages
Power	W	3000 - 3600 max
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	630
Tank Capacity	l	78
Diameter of inlet	mm	60
Filtering surface	cm ²	2960
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	550x600x980
Weight	Kg	28

STANDARD EQUIPMENT

CODE: FTDP00285
WASHABLE POLYESTER
CARTRIDGE 2.960 cm²



CODE: FTDP28755
MESH FILTER



CODE: SECC00116
BUCKET SIEVE 30 L



OPTIONAL ACCESSORIES

Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Anti-oil tool kit ø38-60 mm	PMDT00928
Anti-oil tool kit ø50-60 mm	PMDT00447
Pre separator kit 2" Y connector for tank filling	KTRI05973